

Zeller Presscontrol Systems

Model	Max Material Width	Max Stock Length	Stock Thickness	Speed Cycle/Min recom.	Pulling Capacity
Modell	Max Material- breite	Max Vorschub- länge	Materialdicke	Geschwindigkeit Zyklen/min (empfohlen)	Ziehvermögen
A2	1 – 1/2" 38.1mm	2" 50mm	.002" – .040" .051-1.02mm	260	20 lbs 9.1kg
A4	1 – 1/2" 38.1mm	4" 101mm	.002" – .040" .051-1.02mm	200	20 lbs 9.1kg
A6	1 – 1/2" 38.1mm	2" 152mm	.002" – .040" .051-1.02mm	160	20 lbs 9.1kg
B2	2 – 1/2" 63.5mm	2" 50mm	.002" – .040" .051-1.02mm	230	20 lbs 9.1kg
B4	2 – 1/2" 63.5mm	4" 101mm	.002" – .035" .051-0.89mm	175	20 lbs 9.1kg
C3	3" 76.2mm	3" 76mm	.003" – .075" .076-1.91mm	195	45 lbs 20.5kg
C6	3" 76.2mm	6" 152mm	.003" – .062" .076-1.57mm	140	45 lbs 20.5kg
C12	3" 76.2mm	12" 305mm	.003" – .062" .076-1.57mm	85	45 lbs 20.5kg
D3	4" 101.6mm	3" 76mm	.003" – .075" .076-1.91mm	175	45 lbs 20.5kg
D6	4" 101.6mm	6" 152mm	.003" – .062" .076-1.57mm	135	45 lbs 20.5kg
W6	2" 50.8mm	6" 152mm	.003" – .090" .076-2.29mm	140	100 lbs 45.5kg
W12	2" 50.8mm	12" 305mm	.003" – .062" .076-1.57mm	85	100 lbs 45.5kg
W20	2" 50.8mm	20" 508mm	.003" – .050" .076-1.27mm	50	100 lbs 45.5kg

Zeller Presscontrol Systems

Model	Max Material Width	Max Stock Length	Stock Thickness	Speed Cycle/Min recom.	Pulling Capacity
Modell	Max Material- breite	Max Vorschub- länge	Materialdicke	Geschwindigkeit Zyklen/min (empfohlen)	Ziehvermögen
F4	6" 152mm	4" 101mm	.004" – .075" .1-1.91mm	160	100 lbs 45.5kg
F6	6" 152mm	6" 152mm	.004" – .075" .1-1.91mm	130	100 lbs 45.5kg
F12	6" 152mm	12" 305mm	.004" – .050" .1-1.27mm	70	100 lbs 45.5kg
F20	6" 152mm	20" 508mm	.004" – .035" .1-0.89mm	35	100 lbs 45.5kg
H4	8" 203mm	4" 101mm	.004" – .075" .1-1.91mm	160	100 lbs 45.5kg
H8	8" 203mm	8" 203mm	.004" – .062" .1-1.57mm	105	100 lbs 45.5kg
FX6	6" 152mm	6" 152mm	.005" – .150" .13-3.81mm	105	145lbs 66kg
FX12	6" 152mm	12" 305mm	.005" – .150" .13-3.81mm	60	145 lbs 66kg
L6	12" 305mm	6" 152mm	.005" – .090" .13-2.29mm	105	145 lbs 66kg
L12	12" 305mm	12" 305mm	.005" – .090" .13-2.29mm	60	145 lbs 66kg
P6	16" 406mm	6" 152mm	.005" – .075" .13-1.91mm	105	145 lbs 66kg
P12	16" 406mm	12" 305mm	.005" – .062" .13-1.57mm	60	145 lbs 66kg
LX12	12" 305mm	12" 305mm	.005" – .125" .13-3.18mm	50	250 lbs 114kg